

Home Office
SME Use
Telecommunications
Data Centre



Adept Power Solutions Ltd
Adept House, 65 South Way
Walworth Business Park
Andover, Hampshire
SP10 5AF

E: enquiries@adeptpower.co.uk
T: 01264 351415

Riello Multi Sentry 15kVA 3/3 Phase (18mins)

Part No. MST15-T4

Product Description

Please Note: This UPS will supply 18 minutes runtime at a full load of 13.5kW & is configured as a 3/3 Phase UPS.

The Riello Multi Sentry is a state-of-the-art uninterruptible power supply, achieving the highest possible level of on-line double-conversion performance (VFI-SS-111) as defined within IEC EN 62040-3.

The UPS has been designed to protect critical information and telecommunications systems, networks, services and processes whose operation could be disrupted by poor power quality and/or breaks in their mains power supply.

The Multi Sentry UPS is one of the most efficient UPS available with a minimal impact on its environment and power sources.

ZERO IMPACT SOURCE

MULTI SENTRY UPS are easy to install, especially on sites where there is limited power capacity available, a standby generator and potentially harmonic compatibility issues:

- Low input current distortion - less than 3%
- High input power factor 0.99
- Power walk-in function to achieve progressive rectifier start-up
- Delayed start-up on mains power supply return

MULTI SENTRY also performs the role of a high specification filter, protecting its power supply sources (mains or generator) from any harmonics and reactive power generated by the loads it is powering.

Extended 3 Year Manufacturers Warranty Free of Charge with All Riello UPS.

Features

BATTERY CARE SYSTEM

- The MULTI SENTRY Battery Care System optimises battery performance, to help extend their working life and ensure that the UPS can deliver its full-rated back-up time when called upon in an emergency.
- Battery recharge: MULTI SENTRY is designed to work with VRLA AGM and GEL lead-acid batteries including open-vented types, in addition to Ni-Cads. Specific management features include:
 - One-level recharge to meet the requirements of the most common VRLA AGM batteries
 - Two voltage level recharge meeting the IU characteristic
 - Restricted charging to reduce electrolyte consumption and extend the life of VRLA batteries
- Temperature compensation: to avoid excessive voltage being applied to the batteries in a high ambient
- Battery test: to detect performance degradation and predict battery failure.
- Deep discharge protection: to prevent the batteries being discharged below a level from which they cannot be recovered (especially when discharged over long periods with very low loads).
- Low AC ripple current: from a high-frequency battery charger, to ensure the batteries are not subjected to this damaging element commonly experienced with some other UPS and power supply designs.
- Wide input voltage range: from a rectifier that can work down to less than 40% of its nominal supply rating (at half load), removing the need to discharge the batteries.

FLEXIBILITY

- MULTI SENTRY can be used for a wide range of applications, thanks to its configuration options, flexibility, accessories and performance levels:
 - Suitable for powering capacitive loads, for example Blade servers - without any reduction in active power, from 0.9 leading to 0.9 lagging
 - Modes of operation include: On-Line, Eco, Smart-Active and Stand-By/Off
 - Frequency conversion mode
 - Power Share connections for priority-based load shedding when the mains power supply has failed
 - Cold-start facility to switch the UPS on even without a mains power supply present
 - Extensive back-up time options using battery extension cabinets
 - Optional battery cabinet temperature sensor to assist the temperature compensating charger
 - Optional battery chargers to optimize recharge times
 - Optional dual input supplies
 - Optional isolation transformers for Galvanic isolation and neutral connectivity

ADVANCED COMMUNICATION

- MULTI SENTRY has a large front panel graphic display providing information including: real-time measurements, operating status and

- alarms conditions - in eight different languages
- Advanced multiplatform communication, for all operating systems and network environments: PowerShield³ monitoring and shutdown software included with SNMP agent
- Compatible with TeleNetGuard for the remote assistance service
- RS232 or USB serial port
- Three communication slots for accessories including: network adapters and volt-free contacts
- REPO (Remote Emergency Power Off) to shut down the UPS remotely in an emergency
- Input for connection of an auxiliary contact for an external manual bypass
- Input for synchronisation with an external power source
- Graphic mimic panel display for remote connection.

LOW MANAGEMENT COST

- The MULTI SENTRY design provides exceptional performance and efficiency levels, within a very compact footprint and overall case design:
 - Lowest footprint in its category - 0.26m² for the 20kVA MULTI SENTRY with internal batteries.
 - High efficiency up to 96% - saving up to 35% in dissipated energy in one year compared to a more traditional UPS (91%) resulting in a faster payback period of four years.
 - High output power factor which at 0.9pF (1pF for models 160-200 kVA) provides up to 15% (20% for models 160-200 kVA) more active power compared to a more traditionally sized UPS - providing greater system expansion margin for further load increases.

Specification

Manufacturer	<i>Riello</i>
Power (Va)	<i>15,000VA</i>
Real Power (Watts)	<i>13,500 Watts</i>
Input Phase	<i>Three</i>
Output Phase	<i>Three</i>
Switch Rating (Amps)	<i>63Amps</i>
Weight (Kgs)	<i>320Kg</i>
Depth (mm)	<i>850mm</i>
Width (mm)	<i>440mm</i>
Height (mm)	<i>1,320mm</i>
Communications	<i>Optional SNMP Card</i>
Input Plugs	<i>Hardwired</i>
Output Sockets	<i>Hardwired</i>